FusionServer

2288 V7 Rack Server

Flexible Computing, High Reliability and Security,
Efficient Energy Saving,and Intelligent O&M



xFusion Digital Technologies Co., Ltd.

Rack Server
FusionServer 2288 V7

Introduction



2288 V7 (8 drives) | 2288 V7 (12 drives) | 2288 V7 (24 drives) | 2288 V7 (25 drives)

FusionServer 2288 V7 (2288 V7) is a new-generation 2U 2-socket rack server designed for the Internet, Internet Data Center (IDC), cloud computing, enterprise business, and telecom. It is also ideal for IT core services, virtualization, scientific computing, distributed storage, big data processing, and other complex workloads. The 2288 V7 features low power consumption, high scalability and reliability, easy deployment, and simplified management.

Highlights

Flexible Computing

- Lightweight computing power and energy saving and consumption reduction: Lower-power fans meet heat dissipation requirements, simplifying the air duct design and enabling fast heat dissipation
- Streamlined design and flexible and easy use: Four riser-free standard PCIe slots ensure flexible configuration and tool-free maintenance

High Reliability and Security

- Advanced Extended Volume Air Cooling (EVAC) ensures reliable heat dissipation and stronger temperature adaptation, providing 50% better heat dissipation capability than a single heat sink
- Unique AI memory fault self-healing ensures stable system running and reduces system downtime by 66%
- RoT-based secure boot ensures security everywhere

Efficient Energy Saving

- The unique algorithm is provided for the lowest power consumption of fans and CPUs, saving energy by up to 8% compared with the industry average
- Industry-leading power supply technology for higher efficiency: Three core technologies improve power and efficiency, enabling the industry-leading power conversion rate and the power loss 12.5% lower than the industry average
- Intelligent service awareness and dynamic load adjustment: The CPU working frequency is dynamically adjusted based on the actual service load

Intelligent O&M

- Automatic version push and upgrades can be completed without onsite attendance, improving upgrade efficiency by 20 times
- 75% streamlined deployment steps are performed by tools, improving deployment efficiency by 10 times
- Supports takeover of all vendors' servers, automatic asset location identification, and real-time tracking, 100% accuracy for asset stocktaking

Technical Specifications

Form Factor	2U rack server
Processor	1 or 2 x 4th Gen Intel® Xeon® Scalable processors (Sapphire Rapids) with TDP up to 225 W per processor
Chipset	Emmitsburg PCH
Memory	16 x DDR5 DIMMs, with up to 4800 MT/s speed
Local Storage	Hot-swappable drive configurations: - 8 to 31 x 2.5" SAS/SATA drives/SSDs (up to 31 x 2.5" drives) - 10 to 14 x 3.5" SAS/SATA drives - 4 x NVMe SSDs Flash storage: dual M.2 SSDs
RAID	RAID 0, 1, 10, 1E, 5, 50, 6, or 60; supercapacitors for cache data protection from power failures; RAID level migration, drive roaming, self-diagnosis, and remote web-based configuration
Network	Multiple network expansion capabilities 1 x FlexIO card slot dedicated for 1 x OCP 3.0 NIC, which can be configured as required
PCIe Expansion	Up to 8 x PCIe slots, including 1 x FlexIO slot dedicated for the OCP 3.0 NIC, 1 x slot dedicated for the RAID controller card, and 6 x standard PCIe slots
GPU Card	up to 4 x 75 W half-height half-length GPU cards
Fan Module	4 x hot-swappable counter-rotating fan modules in N+1 redundancy
PSU	2 x hot-swappable Platinum/Titanium PSUs in 1+1 redundancy - 900 W AC Platinum/Titanium PSUs (input: 100 V to 240 V AC, or 192 V to 288 V DC) - 1500 W AC Platinum PSUs 850 W (input: 100 V to 127 V AC) 1500 W (input: 200 V to 240 V AC, or 192 V to 288 V DC) - 1500 W 380 V HVDC PSUs (input: 260 V to 400 V DC) - 1200 W -48 V to -60 V DC PSUs (input: -38.4 V to -72 V DC) - 2000 W AC Platinum/Titanium PSUs 1800 W (input: 200 V to 220 V AC, or 192 V to 200 V DC) 2000 W (input: 220 V to 240 V AC, or 200 V to 288 V DC) 2150 W Titanium PSUs (input: 230 V to 240 V AC, or 230 V to 288 V DC) - 3000 W AC Titanium PSUs 1300 W (input: 90 V AC to 140 V AC; rated voltage: 100 V AC to 127 V AC) 2500 W (input: 180 V AC to 242 V AC; rated voltage: 200 V AC to 220 V AC) 3000 W (input: 198 V AC to 264 V AC or 180 V DC to 300 V DC; rated voltage: 220 V AC to 240 V AC or 240 V DC)
Management	The iBMC chip integrates one dedicated management GE network port, providing comprehensive management features such as fault diagnosis, automatic O&M, and hardware security hardening. - The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0, provides a remote management user interface based on HTML5/VNC KVM; supports out-of-band management functions such as monitoring, diagnosis, configuration, Agentless, and remote control for simplified management - It is optional to configure the FusionDirector management software that provides advanced management features such as five intelligent technologies, enabling intelligent, automatic, visualized, and refined management throughout the lifecycle
OS	FusionOS, Microsoft Windows Server, SUSE Linux Enterprise Server, VMware ESXi, Red Hat Enterprise Linux, CentOS, Oracle, Ubuntu, Debian, and openEuler
Security	Power-on password, administrator password, Trusted Platform Module (TPM) 2.0, security bezel, secure boot, and chassis intrusion detection
Operating Temperature	5°C to 40°C (41°F to 104°F), compliant with ASHRAE Classes A1/A2/A3
Certification	CE, UL, CCC, FCC, VCCI, and RoHS
Installation Suite	L-shaped guide rails, adjustable guide rails, and holding rails
Dimensions (H x W x D)	Chassis with 3.5" drives: 86.1 mm x 447 mm x 798 mm (3.39 in. x 17.60 in. x 31.42 in.) Chassis with 2.5" drives: 86.1 mm x 447 mm x 798 mm (3.39 in. x 17.60 in. x 31.42 in.)

xFusion Digital Technologies Co., Ltd.
Consulting telephone: 400-080-6888
Technical hotline: 400-009-8999
Address: 9th Floor, Building 1, Zensun Boya Square, Longzihu Wisdom Island,
Zhengdong New District, Zhengzhou, Henan Province
Website: www.xfusion.com



Copyrights © xFusion Digital Technologies Co., Ltd 2024. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of xFusion Digital Technologies Co., Ltd.

Trademarks and Permissions

xFUSION and other xFusion trademarks are trademarks of xFusion Digital Technologies Co., Ltd. All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

In this document, "xFusion" is used to refer to "xFusion Digital Technologies Co., Ltd." for concise description and easy understanding, which does not mean that "xFusion" may have any other meaning. Any "xFusion" mentioned or described hereof may not be understood as any meaning other than "xFusion Digital Technologies Co., Ltd.", and xFusion Digital Technology Co., Ltd. shall not bear any liability resulting from the use of "xFusion".

The purchased products, services and features are stipulated by the contract made between xFusion and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties,guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.