
Huawei CloudEngine XH9330-128EO Data Center Switch Datasheet

Huawei CloudEngine XH9330 series switches are next-generation high-density 800GE access switches designed for data center (DC) AI scenarios.



Product Overview



Huawei CloudEngine XH9330 series switches are next-generation high-performance and high-density 800GE access switches designed for DC scenarios. They have an advanced hardware architecture, offer high-density 800GE access ports, support 800GE uplink ports, and deliver a wide range of DC service features. CloudEngine XH9330 series switches can work with XH9000/XH8000 series DC core switches to build an elastic, virtualized, high-quality, and fully-connected 100GE/200GE/800GE DC network (DCN), meeting network requirements of DCs in the cloud era. CloudEngine XH9330 series switches provide high-density 800GE access to help enterprises and carriers build DCNs in the cloud computing era. They can also be used as core or aggregation devices of campus networks.

Product Models and Appearances

CloudEngine XH9330 series switches contain the following model:

CloudEngine XH9330-128EO

Product Appearance	Description

 Port side  Fan module and power module side	128 x 800GE OSFP800 + 2 x 10GE SFP+ ports (uplink and downlink not distinguished)

Product Features

High-Density Access, Providing Superior Capacity

- A CloudEngine XH9330 series switch supports a maximum of 128 800GE high-performance OSFP800 ports. Each 800GE can be split into eight 100GE ports or four 200GE ports. The CloudEngine XH9330 switch can connect to the XH9000/XH8000 series switches through 100GE/200GE/800GE uplinks to build a non-blocking network platform.

Standard Ports, Enabling Open Interconnection

- CloudEngine XH9330 series switches support NETCONF and can interconnect with iMaster NCE-Fabric.
- CloudEngine XH9330 series switches support Ansible — an automatic management and O&M tool — to implement unified provisioning of physical and virtual networks.
- CloudEngine XH9330 series switches are integrated with mainstream cloud platforms (including commercial and open-source cloud platforms) and third-party controllers, enabling flexible service customization and automatic management.

Intelligent O&M Through Collaboration with iMaster NCE-FabricInsight

- CloudEngine XH9330 series switches support telemetry technology to collect device data in real time and send the collected data to iMaster NCE-FabricInsight — the DCN analysis component of Huawei iMaster NCE. Leveraging the intelligent fault identification algorithm, iMaster NCE-FabricInsight can analyze network data, accurately display the real-time network status, locate faults and identify their root causes in a timely and effective manner, and detect network problems that can affect user experience, precisely guaranteeing user experience.
- CloudEngine XH9330 series switches can insert IFIT extension headers into packets, visualize paths, and analyze interface-level packet loss, traffic, and latency to implement high-precision service-level packet loss measurement and facilitate fault demarcation.
- CloudEngine XH9330 series switches support Packet Event. When a device discards packets due to reasons such as abnormal forwarding, specified packet discarding rules, a full buffer, or ACL rule deny actions, or when the latency of packets exceeds a specified threshold, the device reports related flow entries to the iMaster NCE-FabricInsight collector.
- CloudEngine XH9330 series switches support application views. An application view clearly displays the applications, IP subnets, and their indicators and access relationships on the network.

Simplified DCN Deployment via Collaboration with iMaster NCE-Fabric

- CloudEngine XH9330 series switches can interconnect with iMaster NCE-Fabric through standard protocols such as NETCONF and SNMP to adapt to networks and implement automatic network management. This helps to provide more efficient and intelligent operation methods, simplifying network management and reducing the OPEX.

Intelligent Lossless Network, Meeting High Performance Requirements of RoCEv2 Applications

- CloudEngine XH9330 series switches support the iLossless algorithm to eliminate packet loss on the conventional Ethernet. This helps to build a lossless, low-latency, and high-throughput network environment for RoCEv2 traffic, meeting high performance requirements of RoCEv2 applications.
- CloudEngine XH9330 series switches support PFC deadlock prevention. They can identify service flows that may cause PFC deadlocks and change queue priorities of these flows to prevent PFC deadlocks.
- CloudEngine XH9330 series switches support Artificial Intelligence Explicit Congestion Notification (AI ECN). This future-oriented function can intelligently adjust the ECN thresholds of lossless queues based on the live-network traffic model to ensure low latency and high throughput with zero packet loss, maximizing the performance of lossless services.

Licensing

Huawei CloudEngine XH9330 series switches support the CloudFabric XH AI Software business model, which bundles iMaster NCE-Fabric, iMaster NCE-FabricInsight, and CloudEngine XH series switches in a range of typical scenarios. This approach simplifies transactions, provides customers with more functions and value, and protects customers' software investment through Software License Portability.

Feature	XH9000		
	AI Standard Package	AI Enhanced Package(Ascend)	AI Enhanced Package(NVIDIA)
NSLB-S	•	•	•
NSLB-CP		•	
NSLB-DP		•	
device-network coordinated automatic deployment / ZTP-based automatic deployment	•	•	•
basic network management	•	•	•
analysis of faults such as optical link subhealth， PFC deadlock, and PFC storm, as well as network health evaluation		•	•
analysis of inter-GPU/NPU communication paths and status		•	•
device-network collaborative O&M with CCAE		•	

Product Specifications

Item	CloudEngine XH9330-128EO
Port	Jumbo frames
Network convergence	PFC and AI ECN
	RDMA and RoCE (RoCE v1 and RoCE v2)

Programmability	OPS programming
Traffic analysis	NetStream
IP routing	IPv4 dynamic routing protocols such as RIP, OSPF, IS-IS, and BGP
	IPv6 dynamic routing protocols such as RIPng, OSPFv3, IS-ISv6, and BGP4+
IPv6	IPv6 neighbor discovery (ND)
	Path MTU discovery (PMTU)
Reliability	DPFR
	LACP
	BPDU protection
	Hardware-based Bidirectional Forwarding Detection (BFD), with a minimum packet sending interval of 3 ms
	VRRP, VRRP load sharing, and BFD for VRRP
	BFD for BGP, IS-IS, OSPF, and static routing
QoS	Traffic classification based on Layer 2 headers, Layer 3 protocols, and Layer 4 protocol priorities
	ACL, CAR, re-marking, and scheduling
	Queue scheduling modes such as PQ, DRR, and PQ+DRR
Intelligent O&M	Telemetry
	Enhanced ERSPAN
	In-situ Flow Information Telemetry (IFIT)
	Packet Event: packet loss visualization and ultra-long latency visualization
	Statistics collection on the buffer microburst status
Intelligent lossless network	PFC deadlock prevention
	AI ECN
	Enhanced NSLB
Configuration and maintenance	Terminal login through the console port, Telnet, and SSH
	Network management protocols, such as SNMPv1/v2/v3
	File upload and download through FTP and TFTP
	Boot Read-Only Memory (BootROM) upgrade and remote online upgrade
	Hot patching
	User operation logs
	Configuration rollback
	ZTP

Security and management	Command line authority control based on user levels, preventing unauthorized users from using commands
	Defense against DoS, ARP, and ICMP attacks
	Port isolation
	Binding of the IP address, port ID
	Authentication methods, including AAA, LDAP, RADIUS, and HWTACACS
	RMON

Performance and Scalability

Item	Value
Maximum number of MAC address entries	8K
Maximum number of routes (FIB IPv4/IPv6)	480K/240K

Note: This specification may vary between different scenarios. Please contact Huawei for details.

Hardware Specifications

Item		CloudEngine XH9330-128EO
Physical features	Dimensions (H x W x D)	175mm x 442mm × 765mm
	Weight without packaging (full configuration) [kg (lb)]	45 kg
	Switching capacity (Tbps)	204.8
	Forwarding performance (Mpps)	38400
800GE OSFP800 port		128
10GE SFP+ port		2
Management interface	Console port	1 x RJ45 interface
	USB port	1
CPU	Number of cores	32
Power supply	Power modules	2000 W AC&240 V DC power module 2000 W high-voltage DC power module
	Rated input voltage [V]	2000 W AC&240 V DC power module: AC: 100 V AC to 240 V AC, 50/60 Hz; DC: 240 V DC 2000 W high-voltage DC power module: 336 V DC
	Input voltage range [V]	2000 W AC&240 V DC power module: AC: 90 V AC to 290 V AC, 45 Hz to 65 Hz; DC: 190 V DC to 290 V DC 2000 W high-voltage DC power module: 260 V DC to 400 V DC

	Maximum input current	2000 W AC&240 V DC power module: 10 A (100 V AC to 240 V AC); 10 A (240 V DC) 2000 W high-voltage DC power module: 10 A (336 V DC)
	Typical power	1699 W (100% traffic load, short-distance optical modules on half of ports, normal temperature, 4 AC power modules)
	Maximum power	3197 W (100% traffic load, long-distance optical modules on all ports, 40°C,4 AC power modules)
	Frequency (AC, Hz)	50/60
Heat dissipation	Heat dissipation mode	Air cooling
	Number of fans	7
	Heat dissipation airflow	Port-side air intake
Environment specifications	Long-term operating temperature (°C)	0°C to 40°C (0-1800 m) The temperature decreases by 1°C each time the altitude increases by 220 m.
	Storage temperature (°C)	-40°C to +70°C
	Storage relative humidity (RH)	5% to 95%
	Operating altitude (m)	Up to 5000
	Noise at normal temperature	Back-to-front airflow:
	(27°C, sound pressure) (dBA)	63.5 dB(A) on average (maximum: 70.7 dB(A))
	Noise at high temperature (40°C, sound pressure) (dBA)	Back-to-front airflow: 83.5 dB(A) on average (maximum: 90.5 dB(A))
	Surge protection	AC power supply protection: 6 kV in common mode and 6 kV in differential mode DC power supply protection: 4 kV in common mode and 2 kV in differential mode
Reliability	MTBF (year)	26.01
	MTTR (hour)	1.5
	Availability	0.9999934176

Safety and Regulatory Compliance

The following table lists the safety and regulatory compliance of CloudEngine XH9000 series switches.

Certification Category	Description

Safety	EU CE: 2006/95/EC, EN 60950-1 Germany GS: EN 60950-1 CB: IEC 60950-1 USA UL: UL 60950-1 Canada CUL: CSA C22.2 No. 60950-1 Australia RCM: AS/NZS 60950-1 China CCC: GB 4943
Electromagnetic Compatibility (EMC)	EU CE: 2014/30/EU, EN55032, EN 55024, and EN 300386 US FCC: 47CFR Part 15 Canada IC: ICES-003 Australia C-Tick: AS/NZS CIPSR22 Japan VCCI: VCCI-3 and VCCI-4 China CCC: GB 9254
Environment	EU ROHS: 2002/95/EC & 2011/65/EU EU REACH: 1907/2006/EC EU WEEE: 2002/96/EC China RoHS: GB/T 26572
EMC: electromagnetic compatibility; CISPR: International Special Committee on Radio Interference EN: European Standard; ETSI: European Telecommunications Standards Institute CFR: Code of Federal Regulations; FCC: Federal Communication Commission IEC: International Electrotechnical Commission AS/NZS: Australian/New Zealand Standard; VCCI: Voluntary Control Council for Interference UL: Underwriters Laboratories; CSA: Canadian Standards Association	

Ordering Information


Device	Description
XH9330-128EO	XH9330-128EO switch (128*800GE OSFP800,2*10GE SFP+, without fan and power modules)
XH9330-128EO-B	XH9330-128EO-B switch (128*800GE OSFP800,2*10GE SFP+, 6*AC Power Modules, 7* Fans, Portside Intake)
Model	**Description**
FAN-180E-B	FAN-180E-B,Fan box(B,FAN panel side exhaust)
Power Module	**Description**
PAC2KS12-PB	2000W AC&240V DC Power Module (Back to Front,Power panel side exhaust)
PDC2K2S12-PB	2200W DC Power Module (Back to Front, Power panel side exhaust)
PHD2KS12-PB	2000W HVDC power module (back-to-front airflow, panel side exhaust)

Software	
N1-XH9KL1-LIC-STD	Software Charge,N1-XH9KL1-LIC-STD,N1-XH9KL1 Switch Standard Package for the AI Scenarios
N1-XH9KL1STD-SnS1Y	Software annual fee,N1-XH9KL1STD-SnS1Y,N1-XH9KL1 Switch Standard Package for the AI Scenarios-SnS-1 Year
N1-XH9KL1-LIC-ENH	Software Charge,N1-XH9KL1-LIC-ENH,N1-XH9KL1 Switch Enhanced Package for the AI Scenarios
N1-XH9KL1ENH-SnS1Y	Software annual fee,N1-XH9KL1ENH-SnS1Y,N1-XH9KL1 Switch Enhanced Package for the AI Scenarios-SnS-1 Year

Networking and Applications

Typical Application in DCs

On a typical DCN, CloudEngine XH9330 switches work as core switches, whereas CloudEngine XH8000 series switches work as TOR switches and connect to the core switches through 100GE, 200GE or 800GE ports to build an end-to-end and fully-connected 100GE/200GE/800GE network.



More Information

For more information about Huawei products, visit http://e.huawei.com or contact Huawei's local sales office.

Alternatively, you can contact us through one of the following methods:

- Global service hotline: http://e.huawei.com/en/service-hotline
- Enterprise technical support website: http://support.huawei.com/enterprise/
- Service email address for enterprise users: support_e@huawei.com

Copyright © Huawei Technologies Co., Ltd. 2026. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions

HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Technologies Co., Ltd.

Address: Huawei Industrial Base, Bantian, Longgang, Shenzhen,
People's Republic of China

Post code: 518129

Website: e.huawei.com